



# Mineral wool slab ROCKMIN PLUS 75 mm 610 x 500 mm pack 7.32m<sup>2</sup>/12pcs



Brand	ROCKMIN PLUS
Manufacturer	
Dimension	75 mm pack 610 x 1000 mm 7.32m <sup>2</sup> /12pcs
Weight	17.00 kg
SKU	000774
IBB ID	10175

## Product specification

Manufacturer	ROCKWOOL	Unit	pack
Brand	rockmin plus	Dimension	75 mm pack 610 x 1000 mm 7.32m <sup>2</sup> /12pcs
Fire resist	A1	Norm	EN 13162:2012+A1:2015

Universal ROCKMIN PLUS stone wool boards with very good thermal and acoustic parameters are widely used in thermal insulation of single-family houses. They work well as non-flammable insulation in many applications.

### Non-flammable insulation:

ventilated flat roofs and attics,  
wooden ceilings and floors on joists,  
suspended ceilings, e.g. over unheated rooms,  
curtain walls with a skeleton structure with a façade made of panels  
(e.g. siding, boards),  
partition walls

### TECHNICAL PARAMETERS

Reaction to fire class A1  
Sound absorption coefficient  $\alpha_w$ , (AWi)  
0.90 for thick. 50-99mm  
1.00 for thick 100-200mm  
Thermal conductivity coefficient  $\lambda_D=0.037$  W/mK  
Short-term water absorption WS ( $\leq 1$  kg/m<sup>2</sup>)  
Long-term water absorption WL(P) ( $\leq 3$  kg/m<sup>2</sup>)  
Water vapor diffusion resistance coefficient MU1  
Durability of reaction to fire as a function of heat, weathering, aging/degradation - A1  
The value of the thermal conductivity coefficient as a function of aging  $\lambda=0.037$  W/mK