



Mineral wool slab ROCKMIN PLUS 75 mm 610 x 500 mm pack 7.32m²/12pcs



| | |
|--------------|--|
| Brand | ROCKMIN PLUS |
| Manufacturer | |
| Dimension | 75 mm pack 610 x 1000 mm 7.32m ² /12pcs |
| Weight | 17.00 kg |
| SKU | 000774 |
| IBB ID | 10175 |

Product specification

| | | | |
|--------------|--------------|-----------|---|
| Manufacturer | ROCKWOOL | Unit | pack |
| Brand | rockmin plus | Dimension | 75 mm pack 610 x 1000 mm 7.32m ² /12pcs |
| Fire resist | A1 | Norm | EN 13162:2012+A1:2015 |

Universal ROCKMIN PLUS stone wool boards with very good thermal and acoustic parameters are widely used in thermal insulation of single-family houses. They work well as non-flammable insulation in many applications.

Non-flammable insulation:

ventilated flat roofs and attics,
wooden ceilings and floors on joists,
suspended ceilings, e.g. over unheated rooms,
curtain walls with a skeleton structure with a façade made of panels
(e.g. siding, boards),
partition walls

TECHNICAL PARAMETERS

Reaction to fire class A1
Sound absorption coefficient α_w , (AWi)
0.90 for thick. 50-99mm
1.00 for thick 100-200mm
Thermal conductivity coefficient $\lambda_D=0.037$ W/mK
Short-term water absorption WS (≤ 1 kg/m²)
Long-term water absorption WL(P) (≤ 3 kg/m²)
Water vapor diffusion resistance coefficient MU1
Durability of reaction to fire as a function of heat, weathering, aging/degradation - A1
The value of the thermal conductivity coefficient as a function of aging $\lambda=0.037$ W/mK