



Underlay weldable roofing felt Nexler PJ PYE PV200 S40 (PJ 40) 7.5m2



Brand	NEXLER
Manufacturer	
Weight	36.50 kg
Product Code	PZP_PJ_PYE_PV200_S40_7.5
EAN	5903874204251
SKU	003865
Advice IBB	
Application	for waterproofing as a base layer in multi-layer roofing
IBB ID	13722

Product specification

Manufacturer	NEXLER	Unit	roll
Brand	nexler	EAN	5903874204251
Norm	EN 13707:2004+A2:2009 (PN-EN 13707+A2:2012)		

NEXLER PJ PYE PV200 S40 (formerly PJ40) is a weldable underlayment that will provide your roof with solid protection. A roll measuring 7.5x1 meters and 4.0 mm thick is ready to meet your expectations related to durable roofing. Made of fiberglass-reinforced polyester and with modular elasticity. SBS up to -20°C ensures that your roof will be protected against extreme weather conditions.

Technical parameters:

- Tensile force (N/50mm) (Longitudinal/Across): 800 ± 200 [N/5cm]/600 ± 300 [N/5cm] - stable connections of insulation layers.
- Elongation (%) (Along/Across): 50 (±15)/50 (±15) - elasticity protecting against damage and deformation.
- Type of topping: fine-grained - aesthetic appearance and additional protection.

Usage:

PJ PYE PV200 S40 is an ideal solution for multi-layer roof coverings as a base layer, single-layer damp-proof insulation of buildings (type A) and waterproofing of underground parts (type T). Use it for welding or mechanical fastening and enjoy reliable coverage.

Features:

NEXLER PJ PYE PV200 S40 is a weldable underlay felt that is more resistant to overheating thanks to a polyester insert reinforced with glass threads, which guarantees the durability of your roof.