



# Universal acrylic caulk TYTAN PROFESSIONAL, white 280 ml + 30 ml



Brand	TYTAN PROFESSIONAL
Manufacturer	
Weight	0.50 kg
Product Code	10041526
EAN	5902120175710
SKU	000453
IBB ID	8994

## Product specification

Manufacturer	SELENA	Unit	pcs
Brand	tytan professional	Colour	white
EAN	5902120175710		

## Description

Universal acryl is a flexible and universal sealant, used to fill cracks, scratches and gaps in walls and walls before painting.

It is characterized by good adhesion to both wet and dry surfaces, as well as smooth and porous surfaces, i.e. concrete, plaster, brick, wood, plasterboard.

Acryl is practically odorless and can be used both indoors and outdoors. It is resistant to temperature fluctuations, UV radiation and the influence of moisture.

## Benefits

Fast curing

Paintable

Flexible

Resistant to temperature fluctuations, UV radiation and the influence of moisture

Good adhesion to porous surfaces

## Application

Sealing joints, expansion joints and construction gaps

Sealing of building and construction elements made of concrete, wood, metals, bricks, plastics and plasterboards

Joints between the wall and baseboards, stairs, ceiling and electrical sockets

Seals during the assembly of joinery

Minor repairs before painting, filling scratches, cracks in walls, floors, ceilings, corners

## Specification

Color: white, gray, brown

Consistency: thick paste

Curing time: 1 mm / 24 h \*

Temperature resistance (after hardening): -20 ° C to + 80 ° C

Application temperature: from + 5 ° C to + 40 ° C

Processing time: 5-10 minutes \*

Shore A hardness (ISO 868): 40-45