



# Waterproofing protective sealant Torggler Hydro Spray 500ml



Manufacturer	
Country of manufacture	Poland
Weight	1.00 kg
Product Code	501541
EAN	8030334080708
SKU	001034
Advice IBB	
Application	Perfect for sealing leaking roofs, gutters, terrace surfaces, skylights, PVC or metal downpipes
IBB ID	10893

## Product specification

Manufacturer	Torggler	Unit	pcs
EAN	8030334080708	Country of manufacture	Poland
Coverage	approx. 4 m2/can		

**Torggler Hydro Spray it's a solvent-based bituminous waterproofing spray coating.**

For use on all types and types of surfaces. Seals: roofs, gutters, ridge tiles and terraces, skylights, sewage pipes made of PVC or metal, etc. Creates a durable, quick-setting flexible coating.

- Excellent grip
- Long-lasting protective effect
- Flexible
- Quick drying
- Resistant to weather conditions and biological corrosion
- Ready to use
- Easy to apply

### COVERAGE:

approx. 4 m2/can.

### APPLICATION

Suitable for all types of substrates including metal, concrete, plastic and wood; adheres to any type of shape.

Perfect for sealing leaking roofs, gutters, terrace surfaces, skylights, PVC or metal downpipes.

Suitable waterproofing protection of the surfaces of bridges, roofs, pillars, steel structures, tanks, frames of agricultural

machines, bodies automotive.

Useful for sealing ventilation and air conditioning ducts, solar panels and antenna masts passing through the roof, sheets and flashings, as well as to protect porous and absorbent materials.

## **USE**

Check that loose, loose parts, paint, rust and release agents have been removed. Vacuum the surface. Shake the cylinder well until you hear the steel ball moving inside the can. Apply with breaks to maintain an even spray pattern. The drying time of the product depends on the thickness of the applied layer, the type of surface and the ambient conditions. After application, turn the can upside down and spray for 1-2 seconds so that the nozzle remains clean and does not clog.

Drying time (in measurement conditions) 60 - 240 minutes (temperature 23°C and humidity 50%)

Application temperature from +5°C to +35°C

## **WARNINGS**

- Do not apply the product at temperatures below + 5°C
- Do not use in unventilated rooms or inside residential premises.

## **STORAGE**

Store in a dry and covered room. Stored in the original closed packaging at a temperature between +10°C and 30°C, it remains usable for at least 24 months.