



Polystyrene insulation render fixing plug LTX

10x140mm



Manufacturer

Weight

0.01 kg

Product Code

LTX10140(200)

EAN

5907704471493

SKU

2377

IBB ID

2377

Product specification

Manufacturer

WKREȚ-MET

Unit

pcs

EAN

5907704471493

Plastic connector for fixing polystyrene in all substrates according to ETAG 014, in ETICS, EWI systems

Basic parameters of the product:

Diameter [mm] 10

Material Polyethylene / Polyamide + GF

Fastener type Hammered

Body dimensions Lk x dk [mm] 10 x 140

Body material Polyethylene

Screw / bolt / pin / nail material Polyamide + GF

NEW IMPROVED DESIGN

- anchorage: 30 and 50 mm

- Thanks to the new design of the expansion zone, the connector can be installed in all categories of substrates while maintaining high strength parameters

Glass fiber reinforced pin

- Provides high strength during assembly,

The construction of the pin head facilitates assembly, seals the connection pin - connector sleeve

Special connector flange - Greater rigidity of the pressure plate, secure clamping of the fixed material

Innovative design of the sleeve - A large number of "pockets" of glue on the pressure plate increases the adhesion of the adhesive mortar

Mounting type Surface, Substrates according to ETAG014

A - ordinary concrete,

B - full ceramic / silicate brick,

C - perforated (perforated) bricks,

D - elements on lightweight aggregate (LAC),

E - cellular concrete (AAC)

Hole/drill diameter up to [mm] 10

Body flange diameter Dk [mm] 60
Mounting hole depth ho [mm] 40/60*