



Latex paint BIELLUX white matt 10L



| | |
|--------------|--|
| Manufacturer | |
| Weight | 14.70 kg |
| Product Code | BLL10NF |
| SKU | 000915 |
| Advice IBB | |
| Application | For painting interior walls and ceilings |
| IBB ID | 10323 |

Product specification

| | | | |
|--------------|----------------------|-------|----------|
| Manufacturer | PIGMENT Spółka Jawna | Unit | bucket |
| Colour | white | Atest | NIZP-PZH |
| Norm | PN-EN 13300 | | |

WASHABLE LATEX PAINT WITH INCREASED COVERAGE

USE:

Water-dilutable latex paint BASED ON ACRYLIC RESIN intended for painting surfaces of walls and ceilings indoors. It gives a homogeneous, very well-covering, matt, snow-white coating that is permeable to vapors and gases ("breathing" of the walls). It can be used on a variety of construction materials, such as: mineral and polymer plasters (e.g. acrylic), concrete, bricks, gypsum, after appropriate priming: wood-based materials, paper wallpapers, including the so-called rauhphase, giving smooth, flexible coatings.

DIRTY COATINGS CAN BE CLEANED BY A LIGHT WIPE WITH A DAMP CLOTH.

SURFACE PREPARATION AND APPLICATION:

BIELLUX is a ready-to-use paint, the paint should be mixed well before use, only if it thickens, add up to 5% of tap water. Do not add chalk, lime or other materials.

The surface to be painted should be thoroughly cleaned, loose patches of paint removed and degreased. Old coats of glue and lime paints must be removed. Fresh cement-lime plaster can be painted no earlier than 4 weeks after application. Smooth surfaces should be roughened with sandpaper. Fill holes and cracks with BIEL-PUTZ or FILLER putty by Pigment, larger ones with gypsum or cement mortar.

The substrate should be primed with the acrylic preparation BIEL-GRUNT or GRUNDER PC-33 by Pigment.

ADDITIONAL INFORMATION:

The best results can be obtained using the spray method. THE PRODUCT IS NOT INTENDED TO BE COLORED IN A TINTING SYSTEM. If it is necessary to use products from different production batches, it is recommended to mix them together to unify the shade. Any corrections should be made using the "wet on wet" method.

Due to the variety of technologies and raw materials used in products by other manufacturers, the manufacturer is not responsible for the consequences of mixing its product with other products. The paint should be stored in its original and tightly closed packaging.

* The product is available only in white.

SPECIFICATION:

available colors: white

coating: matte

paint: with a roller, brush or after appropriate dilution with spray

use and store at $5 \div 25$ ° C

density according to PN-82 / C-81551: 1.47 g / cm^3

applying the next layer, 20 ° C, humidity relative air 50%: after 2 hours

Brookfield viscosity 20 ± 2 ° C, according to PN-ISO 2555: $8500 \div 10000 \text{ mPa} \cdot \text{s}$

scrub resistance class: 4 according to PN-EN 13300

pH value according to PN-C-04963: 8.0-9.0

solids content PN-EN ISO 3251: $59.0 \div 61.0\%$ by weight

drying time at 23 ± 2 ° C, PN-C-81519: 2 hours

recommended wet film thickness PN-EN ISO 2808: 90-100 μm

the largest grain size (granulation), PN-EN 13300: fine up to 100 μm

water vapor transmission coefficient: high $> 150 \text{ g / (m}^2 \cdot 24 \text{ h)}$; sd $< 0.14 \text{ m}$

recommended number of layers: 2

capacity: $8-10 \text{ m}^2 / \text{L}$

washing tools and diluting: water

Hygienic Certificate NIZP-PZH

Angle. A / a / FW. permissible VOC content for this category: 30 g / L ; the product contains $< 30 \text{ g / L}$

warranty: 24 months from the production date (in original, undamaged packaging)

packaging: 5 L; 10 L.

* The product is also available in the BIO version